



Despriet Gebroeders NV
Looplife Polymers Site
Nijverheidsstraat 2 (B5)
B-2235 Huslhout, Belgium
info@looplife-polymers.eu
www.looplife-polymers.eu

TECHNICAL DATA SHEET

LOOPLIFE r-HDPE

Polyolefins

R-HDPE01C-EBK / GRADE

REPROCESSED HIGH DENSITY POLYETHYLENE / PRODUCT NAME

Description

r-HDPE grades from LOOPLIFE POLYMERS are reprocessed from homogeneous and clean sources of high density polyethylene (HDPE). Product is supplied in the form of pellets.

PHYSICO-CHEMICAL PROPERTIES

Chemical name	High Density Polyethylene			Residual moisture	ppm	Max	1000
Granulometry	pellets/g	25	-	70	Ash content @450°C	%	
Density	g/cm ³				Melt index @230°C, 2,16kg	g/10 min	-
Melt index @190°C, 2,16kg	g/10 min				Melt index @230°C, 5kg	g/10 min	-
Melt index @190°C, 5kg	g/10 min	2	-	3			

MECHANICAL PROPERTIES

Stress at yield	MPa	pending	Tensile modulus	MPa	pending
Stress at break	MPa	pending	IZOD	kJ/m ²	pending
Flex modulus	MPa	pending	Strain at Yield	%	pending
Tensile strength	MPa	pending	Strain at Break	%	pending

SENSORY CHARACTERISTICS

Clarity	Opaque
Shape	Lenticular to cylindrical
Color	Black

PURITY

Other fraction	May contain less than 1% EVOH
----------------	-------------------------------

REGISTRATION

CAS nummer	9002-88-4
------------	-----------

PACKAGING

Standard: Big bag (1200kg Net Weight)

PROCESSING INFORMATION

TRANSPORT STORAGE CONDITIONS

Keep in a dry, well ventilated place. Do not store with oxidizing and self-igniting products
Do not stack big bags

SHELF-LIFE

Shelf-life	36 months
------------	-----------