



Despriet Gebroeders NV  
Looplife Polymers Site  
Nijverheidsstraat 2 (B5)  
B-2235 Huslhout, Belgium  
info@looplife-polymers.eu  
www.looplife-polymers.eu

## TECHNICAL DATA SHEET

# LOOPLIFE r-HDPE

Polyolefins

R-HDPE05C-PBK / GRADE

REPROCESSED HIGH DENSITY POLYETHYLENE / PRODUCT NAME

### Description

r-HDPE grades from LOOPLIFE POLYMERS are reprocessed from homogeneous and clean sources of high density polyethylene (HDPE). Product is supplied in the form of pellets.

### PHYSICO-CHEMICAL PROPERTIES

Chemical name	High Density Polyethylene			Residual moisture	ppm	Max	1000
Granulometry	pellets/g	25	-	70	Ash content @450°C	%	
Density	g/cm <sup>3</sup>				Melt index @230°C, 2,16kg	g/10 min	-
Melt index @190°C, 2,16kg	g/10 min	3	-	6	Melt index @230°C, 5kg	g/10 min	-
Melt index @190°C, 5kg	g/10 min						

### MECHANICAL PROPERTIES

Stress at yield	MPa	pending	Tensile modulus	MPa	pending
Stress at break	MPa	pending	IZOD	kJ/m <sup>2</sup>	pending
Flex modulus	MPa	pending	Strain at Yield	%	pending
Tensile strength	MPa	pending	Strain at Break	%	pending

### SENSORY CHARACTERISTICS

Clarity	Opaque
Shape	Lenticular to cylindrical
Color	Black

### PURITY

Other fraction	May contain less than 2% PP
----------------	-----------------------------

### REGISTRATION

CAS nummer	9002-88-4
------------	-----------

### PACKAGING

Standard: Big bag (1200kg Net Weight)

### PROCESSING INFORMATION

### TRANSPORT STORAGE CONDITIONS

Keep in a dry, well ventilated place. Do not store with oxidizing and self-igniting products  
Do not stack big bags

### SHELF-LIFE

Shelf-life	36 months
------------	-----------